

INSTRUCTIONS FOR USING THE TWO ELEMENT MUG PRESSES

How to set up your mug press:

1. Connect power lead and turn on black power switch on right hand side of control unit.
2. Press MODE  button once. Use left  and right  arrow buttons to set initial low temperature at **160°C**.
3. Press MODE  button again. Use left  and right  arrow buttons to set higher transfer temperature at **176°C**.
4. Press MODE  button again. Use left  and right  arrows to set transfer time at **10**.
5. Press MODE  button one final time and your press is now ready to use.

How to use your mug press:

1. Turn on black power switch on right hand side of control unit.
2. When initial temperature has been reached **160°C** (your mug press will repeatedly beep), place a mug with transfer in the element/sleeve, pull the handle forward to close the press then press the **Square**  start/stop button on the right hand side of the control unit.
3. The temperature will rise to the higher temperature **176°C**, at which point the timer will automatically count down from **10**.
4. When the countdown is complete (i.e. reaches zero) the press will make a continuous beep.
5. Press the **Square**  start/stop button, push the handle back, and carefully remove the mug.
6. The press will drop in temperature to the lower initial temperature **160°C**, and the press is now ready to print the next mug.

NOTE: Please always leave the handle back (open) when the press is on but not being used.

The pressure of the element sleeve can be adjusted by turning the thumb knob next to the element sleeve to ensure consistent firm pressure all around the transfer area.

****Please ensure the mug press is turned off and cool before changing the heat element****

